

OUTDOOR POE GIGABIT SWITCH

Model GW-POE-4G-1S



ABS Plastic Shell



Corrosion Resistance



IP65 Water-Proof



Storage Temperature
-40°C ~ 70°C



Strong Impact Resistance

Flexible Installation Method, Suitable for a Variety of Application Scenarios.



Support Two Installation Methods:
Wall Hanging and Pole Holding.

Weather-Proof PoE Switch




Outdoor Waterproof



Outdoor Lightning Protection

All-in-One

Outdoor PoE Switch



Additional Plugs and Wires Required (Not Included)
14/16/18 Gauge AWG Wire



Chipset		IP175GH
Standard		IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802af, IEEE802.3at
Layer 2 Switching		Backplane Bandwidth: 10Gbps
		Packet Forwarding Speed: 12.96Mbps
		All Ports Speed Forwarding
Port		4*100/1000M Ethernet Port (PoE) +1 * 10/100/1000M UPLINK port +1*SFP port
Power	Voltage	4* PoE port with 802.3at/af standard
	Input Voltage	AC 100-220V
Power Consumption		4W (standby situation)
Maximum Output Power		30W (single port) , Total: 60W
The Size of the MAC Address Table		4K
Features		IEEE 802.3x traffic control under Full-Duplex mode
		Storm control based on the data transmission speed of the port
		PPS-based storm control
Operating Condition	Operating Temperature	-20~60℃
	Storage Temperature	-50~80℃
	Humidity	≤10~90% (non-condensed)

Product Size & Weight:

300*220*30MM



1kg

Package List:

- 1 * GW-PoE-4G-1S
- 1 * Ring
- 1 * Manual



Package Size & Weight:

429X268X94MM
1.2kg

Package Size & Weight:

565*385*280MM
10kg
QTY : 5PCS

